

2WIRE CONVERTER

¬for Ethernet via any pair of wires

SPECIFICATIONS

LAN INTERFACE

- ¬ FastEthernet 100BASE-TX, Auto-MDIX
- ¬ RJ45 connector
- ¬ PoE-PD: IEEE 802.3af and 802.3at
- ¬ PoE-PSE: IEEE 802.3af, max. 25W

2-WIRE INTERFACE

- ¬ Data transfer speed: max. 100 Mbit/s
- ¬ Distance: max. 1000 m
- ¬ pluggable terminal block, 3,5mm pitch

LED INDICATORS

- ¬ Ethernet Link Status
- ¬ Ethernet Activity
- ¬ PoE-Plus Status
- ¬ PoE-PSE Status
- ¬ 2Wire Power
- ¬ 2Wire Link Quality/Activity

POWER SUPPLY

- ¬ PoE PD (802.3af/at)
- ¬ 48-56V DC plug power, inner Ø 2.55mm, outer Ø 5.5mm
- ¬ power consumption app. 1.5W

ENVIRONMENTAL CONDITIONS

- ¬ Temperature Range: -40 °C ~ +60 °C
- ¬ Humidity: 5% ~ 95%, non cond.

COMPLIANCE

- ¬ CE compliant
- ¬ EN55022, EN61000-3-2, EN61000-3-3, EN55024

CONTENT OF DELIVERY


- ¬ 2Wire Set:
 - 1x 2Wire Converter Box PD
 - 1x 2Wire Converter Box PSE
- 2Wire Option (only in combination with Adatis terminal):
 1x 2Wire Converter Box PD
 - 1x Piggyback PCB for Adatis-Terminal (factory installed)


ORDERING INFORMATION

PRODUCT TYPE	ORDER CODE
2Wire Set - Desktop housing	2W5300
2Wire Set - DIN rail housing	2W5200
2Wire PD-Box - Desktop housing	2W5310
2Wire PD-Box - DIN rail housing	2W5210
2Wire PSE-Box - Desktop housing	2W5320
2Wire PSE-Box - DIN rail housing	2W5220




2WIRE OPTION













Adatis GmbH & Co. KG • Forchheimer St. 6 • 90425 Nuremberg • Germany Fon: +49 911 / 255 0975-0 • Fax: +49 911 / 255 0975-9