


## **VideoUP**



Terminal for access control suitable for a standard flush mount box, without moving parts, maintenance free

### **Brand**

Adatis

### **Material**

Glass - FR4 (board)

### **RFID**

- NFC (13.56 MHz, Mifare DESFire EV1)
- Optional extensions for LEGIC and iCLASS
- Encoding MIFARE DESFire EV1 3K3DES/AES

### **PIN code**

- 12 key touch pad, RGB-backlight
- Visual and acoustic feedback for keys pressed

### **Bluetooth**

- BLE 4.1
- Integrated antenna

### **Storage**

Built-in database (Log files, images, etc.) for up to 10.000 entries, expandable via network

### **Power supply**

- Via network (Power-over-Ethernet Standard 802.3af) (version ETHERNET)
- Via over mains 110/230V (version HV/PLC)
- Via 2-wire line (version NV/PLC))
- Via power supply (5VDC, 4W, as accessory)

### **Interfaces**

- 10/100Base-T-Ethernet (RJ45) with PoE (version ETHERNET)
- Ethernet via mains 110/230V with PLC converter (accessory) (version HV/PLC))
- Ethernet via 2-Wire interface (version NV/PLC)
- Wiegand or RS485 interface (version ETHERNET)
- 2x trigger inputs

- 1x relay - e.g. door opener
- Optional BKS wireless module FM01 for control of wireless door locks

### **Operation modes**

- Access control via RFID (NFC) card via built-in multi-standard card-reader, via Bluetooth Low Energy (BLE) with smartphone app and via PIN code; multi-level access control with OR/AND relation
- Color camera for access log and for surveillance
- Moving visual patterns and sounds for operational feedback
- Configuration via web browser
- Management software FaceAdmin, separately available
- API-access via SOAP (ONVIF compatible) for third party management systems

### **Operation software**

Stand-alone operation without any PC, no operation software necessary; however system can be implemented in (third party) management systems.

### **Compliance**

CE, EMV (EN 55011, EN 55022, EN 500081)

### **Temperature range**

-20°C to +40°C

### **Contents of delivery**

- VideoUP device (black or white, other colors on request)
- 3 MIFARE cards

### **Theft and sabotage protection**

No access control function when dismantling glass frame

### **Mounting**

- Surface mounting via standard flush mount box
- Suitable for all 55mm standard switch programs

### **Dimensions**

with switch frame: 95 mm (B) x 95 mm (H) x 42 mm (T)

### **Weight**

0,64 kg

### **Additional notes**

- Fanless
- No moving parts - maintenance free

**Product information at [www.adatis.com](http://www.adatis.com)**

**Brand:** Adatis  
**Type:** VideoUP

# TENDER SPECIFICATIONS



Order No: 5510 version „ETHERNET“  
Order No: 5520 version „HV/PLC“  
Order No: 5530 version „NV/PLC“

AMOUNT: ..... UNIT: Item SP: ..... TP: .....