


FaceUP

Terminal for biometric access control suitable for a standard flush mount box, without moving parts, maintenance free

Brand

Adatis

Material

Glass - FR4 (board)

Biometry

- 2.5D face recognition for indoor use (bis 50.000 lux)
- Works in complete darkness
- NIR illumination for ambient light independence
- Aborting by photo impossible
- Storage of templates in the device, in external database or on RFID card, no reconstruction of the face possible

RFID

- NFC (13.56 MHz)
- Mifare Classic, Mifare Desfire EV1
- Optional extensions for LEGIC and iCLASS available as ordering options

PIN code

- 12 key touch pad, RGB-backlight
- Visual and acoustic feedback for keys pressed

Bluetooth (available 2019)

- BLE 4.1
- Integrated antenna

Storage

Internal database (log files, images, etc.) for up to 1,000 entries, expandable via network

Power supply

- via network cable (Power-over-Ethernet Standard 802.3af), alternatively via power supply (6-56V) (type ETHERNET)
- via 110/230V line (type HV/PLC)

- via 2wire line (type NV/PLC)

Interfaces

- 10/100Base-T-Ethernet (RJ45) with PoE (type ETHERNET)
- Ethernet via 110/230V line with powerline adapter (type HV/PLC)
- Ethernet via 2wire line (type NV/PLC)
- Wiegand
- 2x Trigger input
- 1x Relay - e.g. door opener

Operation modes

- Access control via biometric 2.5D face recognition, via RFID card via built-in multi-standard cardreader, via Bluetooth Low Energy (BLE) with smartphone app (available 2019) and via PIN code; up to 4-tier access control with OR/AND relation
- Moving visual patterns and sounds for operational feedback
- Color camera for log files and surveillance
- Configuration via web browser
- Management software FaceAdmin, separately available
- API-access via XML-RPC for third party management systems

Operation software

Stand-alone operation without any PC, no operation software necessary; system can be implemented in (third party) management systems.

Compliance

CE, EMV (EN 55011, EN 55022, EN 500081)

Temperature range

-20°C to +40°C

Contents of delivery

- FaceUP device including glass frame (black or white)
- 2 pcs. MIFARE cards
- Connection cable and adapter depending on order type

Theft and sabotage protection

Alarm message and deactivation of the access function on removal of the glass frame

Mounting

- mounting via standard flush mount box
- Suitable for all 55mm standard switch programs
- Working distance: about 40 - 60 cm

Dimensions

including frame: 95 mm (W) x 95 mm (H) x 42 mm (D)

TENDER SPECIFICATION



Weight

0,64 kg

Additional notes

- Fanless
- No moving parts - maintenance free

Product information at www.adatis.com

Brand: Adatis
Type: FaceUP

Order No: 6510 tpye ETHERNET
Order No: 6520 type HV/PLC
Order No: 6530 type NV/PLC

AMOUNT: UNIT: Item SP: TP: